


WOOD NAILERS INSTALLED WITH BOND BREAKERS AND FASTENED AS SPECIFIED OR REQUIRED BY CODE OR INDUSTRY STANDARDS TO RESIST DESIGN LOADS AND CORROSION OF STEEL DECKING, FASTENERS AND METAL EDGING.

NOTES:

1. DETAIL TO BE USE IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.
2. SOPREMA ADHESIVES, CEMENTS, MASTICS, PRIMERS AND SEALANTS ARE REQUIRED WHERE INDICATED.
3. WHEN A TWO-PLY FLASHING SYSTEM IS SPECIFIED; OVERLAP FIRST MEMBRANE WALL FLASHING PLY A MIN. 3" BEYOND FASTENERS OF THE BASE FLASHING PLIES. THE WALL COVERING MEMBRANE(S) ARE HEAT WELDED ONTO A PROPERLY PREPARED SUBSTRATE. DO NOT BOND SELF-ADHESIVE MEMBRANES TO CMU OR BRICK SURFACES. MAX. SA MEMBRANE HEIGHT 24" (610mm)

		310 QUADRAL DRIVE	
		WADSWORTH, OHIO 44281	
		(330) 334-0066	
TITLE			
HIGH WALL MEMBRANE COVERING			
SCALE	DWN	CHK	APPROVAL DATE
NONE	DMT	BS	4/13/06
DRAWING NUMBER			REV
AHWBF-001			0

** USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.