


WOOD NAILERS INSTALLED WITH BOND BREAKERS AND FASTENED AS SPECIFIED OR REQUIRED BY CODE OR INDUSTRY STANDARDS TO RESIST DESIGN LOADS AND CORROSION OF STEEL DECKING, FASTENERS AND METAL EDGING.

**NOTES:**

1. DETAIL TO BE USE IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.
2. SURFACE MOUNT FLASHING MUST BE INSTALLED TO HARD, SMOOTH CLEAN NON-POROUS SUBSTRATE.
3. DO NOT APPLY SEALANT OVER ASPHALT OR OTHER MATERIALS THAT WILL PREVENT PROPER ADHESION.
4. SOPREMA DOES NOT WARRANT WATER TIGHTNESS OF THE FLASHING TERMINATION UNLESS THE ALSAN FLASHING SYSTEM IS USED TO STRIP-IN TERM BAR.
5. WHEN A TWO-PLY FLASHING SYSTEM IS SPECIFIED; OVERLAP THE WALL MEMBRANE(S) COVER A MIN. 3" BEYOND FASTENERS OF THE BASE FLASHING PLIES. THE WALL MEMBRANE(S) COVER IS HEAT WELDED ONTO A PROPERLY PREPARED SUBSTRATE. DO NOT BOND SELF-ADHESIVE MEMBRANES TO CMU OR BRICK SURFACES. MAX. SA MEMBRANE HEIGHT 24" (610mm)

		310 QUADRAL DRIVE	
		WADSWORTH, OHIO 44281	
		(330) 334-0066	
TITLE			
PARAPET HORIZONTAL TERMINATION			
SCALE	DWN	CHK	APPROVAL DATE
NONE	DMT	PR	9/1/05
DRAWING NUMBER			REV
AHWBF-002			0

\*\* USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.