



NOTES:

1. DETAIL TO BE USE IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.
2. SOPREMA ADHESIVES, CEMENTS, MASTICS, PRIMERS AND SEALANTS ARE REQUIRED WHERE INDICATED.
3. WHEN A TWO-PLY FLASHING SYSTEM IS SPECIFIED; OVERLAP FIRST MEMBRANE WALL FLASHING PLY A MIN. 3" BEYOND FASTENERS OF THE BASE FLASHING PLIES. THE WALL COVERING MEMBRANE(S) ARE HEAT WELDED ONTO A PROPERLY PREPARED SUBSTRATE. DO NOT BOND SELF-ADHESIVE MEMBRANES TO CMU OR BRICK SURFACES. MAX. SA MEMBRANE HEIGHT 24" (610mm)

		310 QUADRAL DRIVE WADSWORTH, OHIO 44281 (330) 334-0066	
TITLE HIGH WALL TWO PLY MEMBRANE COVERING			
SCALE NONE	DWN DMT	CHK BS	APPROVAL DATE 11/28/06
DRAWING NUMBER AHWBF-007			REV 0

** USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.