

SEE APPROPRIATE METAL PARAPET CAP DETAIL

ADHERED SINGLE-PLY MEMBRANE

SOPREMA BONDING ADHESIVE

SHEET-METAL COUNTERFLASHING (PRIME PRIOR TO THE ADHESION OF ANY MEMBRANE)

OPTIONAL: INSTALL COMPRESSIBLE ELASTOMERIC SEALANT OR TAPE TO SPAN IRREGULARITIES

TERMINATION BAR FASTENED WITH APPROPRIATE FASTENERS 12" O.C. (MAXIMUM) OR FASTENER AND 2" DIAMETER PLATE 8" O.C.

SOPREMA SBS MEMBRANE ROOF SYSTEM

COVERBOARD INSULATION (IF REQUIRED)


THERMAL INSULATION (IF REQUIRED)

ROOF DECK

8" MINIMUM  
24" MAXIMUM  
FLASHING HEIGHT

NOTES:

1. DETAIL TO BE USE IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.
2. THIS DETAIL SHOULD BE USED ONLY WHERE THE DECK IS SUPPORTED BY THE WALL.
3. COUNTERFLASHING DETAIL MAY BE A TWO-PIECE REGLET AND COUNTERFLASHING.

		310 QUADRAL DRIVE WADSWORTH, OHIO 44281 (330) 334-0066	
		TITLE BASE FLASHING W/ CF @ HIGH WALL	
SCALE	DWN	CHK	APPROVAL DATE
NONE	DMT	BS	1/16/09
DRAWING NUMBER			REV
AHWBF-008			1

\*\* USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.