


- POLYURETHANE CAULKING (BY OTHERS).
- EXISTING COUNTERFLASHING BEND UP AS REQUIRED TO PREPARE SURFACE, CLEAN & APPLY ALSAN LIQUID MEMBRANE. RETURN TO ORIGINAL POSITION AFTER MEMBRANE CURES.
- PREPARE, LEVEL & PATCH SUBSTRATE W/ ACCEPTABLE PATCHING MORTAR PRIOR TO APPLICATION OF ALSAN PRIMER AND LIQUID MEMBRANE (TYP.)
- ALSAN FULLY REINFORCED LIQUID MEMBRANE (FLASHING GRADE) EXTEND 4" (10cm) MIN. HORIZONTALLY ONTO PREPARED AND PRIMED SUBSTRATE (SEE NOTE #2).
- FULLY ADHERED SBS MEMBRANE SYSTEM (AS SPECIFIED).
- MIN. 1/4" SOPRABOARD OR APPROVED MIN. 1/2" RECOVERY BOARD (BY OTHERS) SECURELY ATTACHED TO SUBSTRATE.
- MIN. 1" RIGID BOARD INSULATION SECURELY FASTENED TO SUBSTRATE.

NOTES:  
 1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.

		310 QUADRAL DRIVE WADSWORTH, OHIO 44281 (330) 334-0066					
		TITLE LIQUID FLASHING OVER SBS W/CF LOW FLASHINGS (INSULATED)					
SCALE	NONE	DWN	PBF	CHK	KD	APPROVAL DATE	11/11/10
DRAWING NUMBER	BI-7M					REV	0

\*\* USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.