


- NOTES:
1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, COLSTIC PDS AND APPROVED DETAILS.
 2. SEE DETAIL CXM-001 NOTES 2 & 3 FOR END LAP, (T) JOINTS AND FLASHING TIE-IN WATERTIGHT SEAL.
 3. MEMBRANE INSTALLATION MUST NOT PREVENT VENTILATION OF EXISTING STRUCTURE.
 4. WHEN PHASE CONSTRUCTING, BASE MEMBRANE PLY MUST BE CLEAN, DRY AND FREE OF ANY LATENT MOISTURE PRIOR TO PRIMER AND CAP SHEET APPLICATION.
 5. COLSTIX™ SERIES FIELD CAP MEMBRANE PLY HAS A SELF-ADHESIVE UNDERSIDE WITH THE RELEASE FILM REMOVED PRIOR TO ADHERING THE CAP SHEET TO THE PRIMED COLSTIX™ SERIES FIELD BASE MEMBRANE PLY. THE FIELD BASE MEMBRANE PLY HAS EITHER A SELF-ADHESIVE OR PARTIAL SELF-ADHESIVE RIBBON UNDERSIDE WITH THE RELEASE FILM REMOVED PRIOR TO ADHERING THE BASE PLY TO AN ACCEPTABLE SUBSTRATE OR PRIMED SUBSTRATE. SEE CXM DETAILS.

		310 QUADRAL DRIVE	
		WADSWORTH, OHIO 44281	
		(330) 334-0066	
TITLE COLSTIX™ (T) Joint and End Lap Layout			
SCALE NONE	DWN DMT	CHK PR	APPROVAL DATE 5/1/05
DRAWING NUMBER CXM-003			REV 0

** USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.