


NOTES:

1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.
2. A FULLY REINFORCED LIQUID MEMBRANE SYSTEM IS DEFINED AS AN ASSEMBLY CONSISTING OF TWO LIQUID RESIN APPLICATIONS & FABRIC REINFORCEMENT INSTALLED BETWEEN THE RESIN LAYERS. REFER TO DETAIL A-1 FOR ADDITIONAL INFORMATION.
3. 4" WIDE ALSAN FULLY REINFORCED LIQUID MEMBRANE STRIP APPLIED OVER ALL RECOVERY BOARD JOINTS, ANGLE CHANGES AND VOIDS. FILL JOINTS & VOIDS W/ACCEPTABLE PATCHING MORTAR OR PASTE TO PRIOR TO APPLICATION OF LIQUID MEMBRANE STRIPS.

		310 QUADRAL DRIVE WADSWORTH, OHIO 44281 (330) 334-0066						
		TITLE ROOF DRAIN LIQUID FLASHING W/INSULATION AND MOD BIT						
SCALE	NONE	DWN	PBF	CHK	KD	APPROVAL DATE	11/11/10	
DRAWING NUMBER	DI-1aM						REV	0

\*\* USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.