



METAL GRAVEL EDGE – ABRABE & CLEAN FLANGE W/ SPECIFIED CLEANER & SET IN BED OF ACCEPTABLE SEALER.

ALSAN FULLY REINFORCED LIQUID MEMBRANE (FLASHING GRADE) EXTEND FULL WIDTH OF FLANGE & 4" (10cm) MIN. HORIZONTALLY ONTO PREPARED SURFACE.

FASTENERS 4" (10cm) O.C., STAGGERED 1".

ALSAN FULLY REINFORCED LIQUID MEMBRANE (SEE NOTE #2).

1/4" HEM

PREPARE, LEVEL & PATCH SUBSTRATE W/ACCEPTABLE PATCHING MORTAR PRIOR TO APPLICATION OF ALSAN LIQUID MEMBRANE SYSTEM (TYP).

CONTINUOUS CLEAT, FASTENED 6" (15cm) (MAX.)

NOTES:

1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.
2. A FULLY REINFORCED LIQUID MEMBRANE SYSTEM IS DEFINED AS AN ASSEMBLY CONSISTING OF TWO LIQUID RESIN APPLICATIONS & FABRIC REINFORCEMENT INSTALLED BETWEEN THE RESIN LAYERS. REFER TO DETAIL A-1 FOR ADDITIONAL INFORMATION.

		310 QUADRAL DRIVE WADSWORTH, OHIO 44281 (330) 334-0066					
		TITLE GRAVEL EDGE FLASHING					
SCALE	NONE	DWN	PBF	CHK	BS	APPROVAL DATE	5/07/09
DRAWING NUMBER	E-1					REV	0

\*\* USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.