



METAL GRAVEL EDGE – ABRASE & CLEAN FLANGE W/ SPECIFIED CLEANER & SET IN BED OF ACCEPTABLE SEALER.

ALSAN FULLY REINFORCED LIQUID MEMBRANE (FLASHING GRADE) EXTEND FULL WIDTH OF FLANGE & 4" (10cm) MIN. HORIZONTALLY ONTO PREPARED SURFACE. (SEE NOTE #2).

FASTENERS 4" (10cm) O.C., STAGGERED 1".

FULLY ADHERED SBS MEMBRANE SYSTEM (AS SPECIFIED).

CONTINUOUS CLEAT, FASTENED 6" (15cm) (MAX.)

GUTTER & SUPPORT STRAPS BY OTHERS. EXPOSED FASTENERS MUST BE FASTENED ALONG VERTICAL FACE OF DRIP EDGE & USE ACCEPTABLE SEALING WASHERS.

- NOTES:
1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.
 2. A FULLY REINFORCED LIQUID MEMBRANE SYSTEM IS DEFINED AS AN ASSEMBLY CONSISTING OF TWO LIQUID RESIN APPLICATIONS & FABRIC REINFORCEMENT INSTALLED BETWEEN THE RESIN LAYERS. REFER TO DETAIL A-1 FOR ADDITIONAL INFORMATION.

		310 QUADRAL DRIVE WADSWORTH, OHIO 44281 (330) 334-0066					
		TITLE GUTTER EDGE LIQUID FLASHING OVER MOD BIT					
SCALE	NONE	DWN	PBF	CHK	KD	APPROVAL DATE	11/11/10
DRAWING NUMBER	E-3M					REV	0

** USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.