


NOTES:

1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.
2. UNLESS OTHERWISE NOTED, FASTENER DENSITIES ARE DETERMINED EITHER BY PROJECT SPECIFICATION, DESIGN VELOCITY PRESSURES IN ACCORDANCE WITH CURRENT EDITION OF ASCE 7 OR AUTHORITY HAVING JURISDICTION (AHJ).
3. FASTENING PLATES MUST BE PRIMED WITH ELASTOCOL 500 OR ELASTOCOL 600c.

CONVERSIONS	
6" = 152mm	30" = 762mm
12" = 305mm	36" = 914mm
18" = 457mm	42" = 1.07m
24" = 610mm	48" = 1.2m

		310 QUADRAL DRIVE WADSWORTH, OHIO 44281 (330) 334-0066	
		TITLE 14 FASTENERS PER 4' X 4' BOARD	
SCALE 1"=1'	DWN DMT	CHK BS	APPROVAL DATE 9/11/06
DRAWING NUMBER IFP/FMG-017			REV 0

** USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.