

Elastocol 400



Description

Elastocol 400 primer is a solvent based primer composed of a blend of elastomeric polymers. Elastocol 400 is typically applied to concrete, metal or wood substrates that are properly prepared per Soprema general requirements.

Substrate

- Asphalt Membranes
- Concrete
- Gypsum Board (special facers)
- Masonry
- Metal
- Plywood
- Polyisocyanurate (special facers)
- Specific Membranes
- Sopraboard
- Wood
- Wood Composite
- Wood Fiber Board



Advantages

- Quick Drying
- Available in five (5) gallon (18.1 L) pails.
- Available in aerosol cans for small detail priming with quick dry time, self adhered applications.
- Quick dry surface preparation primer for projects that are phase constructed.
- During warm and/or sunny weather, Elastocol 400 can be used as a self adhered primer on top of a self adhered field base membrane or inner ply on horizontal applications ONLY prior to a self adhesive inner ply or field cap membrane ply(s) being installed.
- FM approvals, Underwriters Laboratories, Inc. File #R11436; ISO-9002
- Included in Soprema Project Warranty Agreement offerings.

Uses

Elastocol 400 primer is a general all purpose primer that increases adhesion to various substrates. Typical concrete, metal or wood substrates are properly prepared, clean and dry prior to Elastocol 400 primer applications. For Elastocol 400 primer in pails, the application rate is 100-150 square feet per gallon prior to hot asphalt, cold adhesive or heat welded membrane installations. For Elastocol 400 primer in aerosol cans, the application rate may vary by user and substrate being primed. Elastocol 400 in aerosol cans is perfect for detail application projects such as new penetration and through-wall scupper additions and other small or hard to get to areas.

*The Building
Envelope
Company*