


- NOTES:
1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS AND APPROVED DETAILS.
 2. ALSAN[®] FLASHING 30 WET MILS COVERAGE RATE (22 DRY MILS) IS 1.87 GALS/100FT². ALL COVERAGE RATES ARE APPROXIMATE, THEORETICAL AND DO NOT ACCOUNT FOR WASTE, SPILLAGE, IRREGULAR SURFACES AND APPLICATION TECHNIQUES THAT CAN ALSO VARY WITH INSTALLER. RATES MAY ALSO VARY DEPENDING UPON MATERIAL AND AMBIENT TEMPERATURE(S). SURFACE FINISH AND POROSITY OF THE SUBSTRATE.
 3. IF ALSAN[®] FLASHING SYSTEM IS NOT COMPLETED WITHIN SEVEN DAYS, SEE APPLICATION AND COVERAGE DIRECTIONS FOR SOPREMA PRIMER THAT IS REQUIRED.
 4. EXISTING STANDING WATER FIELD CONDITIONS ARE THE BUILDING OWNER/SPECIFIER'S RESPONSIBILITY TO ELIMINATE OR REDUCE. NEITHER THE AESTHETIC APPEARANCE (WEAR & TEAR) OF THE COATING LAYER(S) NOR MOISTURE TRAPPED BETWEEN THE COATING LAYER(S) AND THE ORIGINAL CAP SHEET ARE "COVERED REPAIRS" ACCORDING TO THE TERMS & CONDITIONS OF THE SOPREMA WARRANTY AGREEMENT.

		310 QUADRAL DRIVE WADSWORTH, OHIO 44281 (330) 334-0066		
		TITLE ALSAN [®] FLASHING – PONDING PROTECTION		
SCALE	NONE	DWN DMT	CHK PR	APPROVAL DATE 9/1/05
DRAWING NUMBER				REV
MISC-009				0

** USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.