



MATERIAL SAFETY DATA SHEET

SOPRAROCK DD

HMIS	PROTECTIVE CLOTHING	TRANSPORT OF DANGEROUS GOODS								
<table border="1"> <tr><td>1</td><td>HEALTH</td></tr> <tr><td>0</td><td>FLAMMABILITY</td></tr> <tr><td>0</td><td>REACTIVITY</td></tr> <tr><td>B</td><td>PROTECTIVE EQUIPMENT</td></tr> </table>	1	HEALTH	0	FLAMMABILITY	0	REACTIVITY	B	PROTECTIVE EQUIPMENT		NOT REGULATED
1	HEALTH									
0	FLAMMABILITY									
0	REACTIVITY									
B	PROTECTIVE EQUIPMENT									

SECTION II. CHEMICAL PRODUCT AND COMPANY INFORMATION

Product name:	SopraRock DD, SopraRock DD Cant Strip
Use:	Commercial, industrial and residential insulation
Manufacturer:	Soprema, Inc. 310 Quadral Drive Wadsworth, Ohio 44281 UNITED STATES
Distributor:	Soprema, Inc. 310 Quadral Drive Wadsworth, Ohio 44281 UNITED STATES
In case of emergency:	SOPREMA (8:00am to 5:00pm - Eastern time): (800) 356-3521 CHEMTREC (USA) (24h.): (800) 424-9300 CANUTEC (Canada): (613) 996-6666

EMERGENCY OVERVIEW!!!

Acrid smoke may be generated during a fire.
Exposure to dust may be irritating to the eyes, nose and throat.

SECTION II. COMPOSITION AND INFORMATION ON INGREDIENTS

Component	CAS#	% by weight
Mineral fiber	RN 65997-17-3	94-99
Cured urea extended phenolic formaldehyde binder	25104-55-6	1-6

SECTION III. POTENTIAL HEALTH EFFECTS	
Inhalation	Temporary mechanical irritation of the upper respiratory tract (scratchy throat, coughing, congestion) may result from exposures to dusts and fibers in excess of applicable exposure limits.
Skin contact	Dusts and fibers may cause temporary mechanical irritation (itching) or redness to the skin.
Eye contact	Dusts and fibers may cause temporary mechanical irritation (itching) or redness to the eyes.
Ingestion	Ingestion of this product is unlikely and not intended under normal conditions of use. Ingestion of this product may cause gastrointestinal irritation.
Existing medical conditions	Pre-existing chronic eye, skin and respiratory conditions may temporarily worsen due to exposure to dusts and fibers.

SECTION IV. FIRST AID MEASURES	
SKIN	Do not rub or scratch. Rinse under running water prior to washing with mild soap and water. Use a washcloth to help remove fibres. If irritation persists, consult a physician.
EYES	Flush with water for 15 minutes. Do not rub the eyes. Consult a physician if irritation persists.
INHALATION	Remove the affected person to fresh air. Drink water, and blow nose, to clear dusts and fibres from throat and nose. If irritation persists, consult a physician.
INGESTION	Ingestion of this product is unlikely and not intended under normal conditions of use. If it does occur, rinse mouth with plenty of water to help remove dust and fibres, and drink plenty of water to help reduce potential gastrointestinal irritation. Do not induce vomiting unless directed to do so by a physician.

SECTION V. FIRE-FIGHTING MEASURES	
The products are non-combustible and do not pose a fire hazard. However, packaging material may burn.	
Flash point	None
Auto ignition temperature	N/A
Lower explosive limit	N/A
Upper explosive limit	N/A
Combustion products	Carbon dioxide, carbon monoxide and trace gas
Explosion properties	N/A
Extinguishing media	Water, foam, carbon dioxide or dry powder.
Hazardous combustion products	N/A
Fire fighting equipment	Observe normal fire fighting procedures

SECTION VI. ACCIDENTAL RELEASE MEASURES	
Containment Procedures: Pick up large pieces and scoop up dusts and fibers after they have settled out of air. These materials will disperse and settle along the bottom of waterways and ponds. It cannot easily be removed once it is waterborne, but is considered non-hazardous in water.	
Cleanup Procedures: Use OSHA-recommended work practices and protective equipment as described in Section 8 of this Material Safety Data Sheet. Avoid generating airborne dusts and fibers during cleanup. Do not use compressed air. Vacuum dusts and fibers. Place material in an appropriate container for disposal as non-hazardous waste.	
Response Procedures: Isolate area. Keep unnecessary personnel away. If dry methods or compressed air are used to collect dusts and fibers, all personnel in the area should wear OSHA-approved protective equipment (see Section 8 of this Material Safety Data Sheet).	

SECTION VII. HANDLING AND STORAGE

General Precautions:

Utilize OSHA-recommended work practices and protective equipment when using the products (see Section 8 of this Material Safety Data Sheet).

Handling:

Unpack material at application site to avoid unnecessary handling of product.

Keep work areas clean. Avoid unnecessary handling of scrap material and debris by placing such materials in suitable containers, which should be kept as close to the work area as possible.

Ensure good ventilation. Local exhaust ventilation may be required if the method of use produces dust levels which exceed applicable exposure limits (see Section 8 of this Material Safety Data Sheet).

Avoid excessive eye and skin contact with dusts and fibers.

Use recommended cleanup procedures to avoid buildup of dusts and fibers in the work area.

Storage:

Keep material in original packaging until it is to be used.

Store material to protect against adverse conditions including precipitation.

SECTION VIII. EXPOSURE CONTROLS / PERSONAL PROTECTION

General Product Information:

Follow all applicable exposure limits. Local regulations may apply. Roxul recommends that users of the products adhere to the OSHA-recommended PEL of 1 f/cc TWA (fibers longer than 5 µm with diameters less than 3 µm). This recommended PEL, together with recommended work practices and personal protective equipment, were adopted in a Health and Safety Partnership Program (HSPP) agreement in 1999 between OSHA and the North American Insulation Manufacturers Association (NAIMA), of which Roxul is a member. Adherence to the OSHA-recommended PEL, work practices and protective equipment in the HSPP is expected to provide appropriate protection against all inhalation-related health risks that may be associated with exposures to mineral wool fibers (ACGIH 1997; NAIMA 1999; OSHA 1999; National Research Council 2000, IARC 2001), and to minimize eye and skin irritation.

Component Exposure Limits:

Source	Legal or recommended exposure limit	Exposure
OSHA	1 f/cc TWA (recommended)	Synthetic Vitreous Fibers, > 5 µm length, < 3 µm diameter
ACGIH	1 f/cc TWA (threshold limit value – TLV)	Synthetic Vitreous Fibers, > 5 µm length, < 3 µm diameter
OSHA	15 mg/m ³ TWA-PEL (total particulate) 5 mg/m ³ TWA-PEL (respirable particulate)	Inert dust and particulates not otherwise regulated
ACGIH	10 mg/m ³ TWA-TLV (inhalable particulate) 3 mg/m ³ TWA-TLV (respirable particulate)	Particulates not otherwise classified, containing no asbestos and <1% crystalline silica

Equipment and Work Practices:

Follow OSHA-recommended equipment and work practices. A complete copy of these practices can be obtained from Roxul Inc. (see Section 1 of this Material Safety Data Sheet), and is available on the OSHA website (<http://www.osha.gov/SLTC/syntheticmineralfibers>).

Follow OSHA-recommended safe handling practices listed in Section 7.2 above.

Where feasible, general dilution ventilation or local exhaust ventilation should be used as necessary to maintain exposures below applicable exposure limits. Dust collection systems should be used in cutting or machining operations and may be needed when using power tools.

Follow OSHA-recommended work practices when fabricating, installing or removing product.

Eyes/face

Wear safety goggles or safety glasses with side shields.

SECTION VIII. EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal Protective equipment:

Respiratory	<p>General: If dust levels exceed applicable exposure limits, wear a NIOSH certified dust respirator with an efficiency rating of N95 or higher. Use disposable face masks complying with NIOSH respirator standards, such as a 3M Model 8210 (or 8710) (3M Model 9900 in high humidity environments) or equivalent. For exposures up to five times the established exposure limits use a quarter-mask respirator, rated N95 or higher; and for exposures up to ten times the established exposure limits use a half-mask respirator (e.g. MSA's DM-11, Racal's Delta N95, 3M's 8210), rated N95 or higher. For exposures up to 50 times the established exposure limits use a full-face respirator, rated N99 or higher.</p> <p>Specific Operations: Wear a NIOSH certified dust respirator with an efficiency rating of N95 or higher, such as a 3M Model 8210 (or 8710) (3M Model 9900 in high humidity environments) or equivalent, when fabricating, installing or removing product.</p>
Skin	Wear loose fitting, long sleeved and long-legged clothing to prevent irritation. A head cover is also recommended, especially when working with material overhead. The use of suitable gloves is also recommended. Skin irritation cannot occur if there is no contact with the skin. Do not tape sleeves or pants at wrists or ankles. Remove fibers from the work clothes, before leaving work to reduce potential skin irritation. If working in a very dusty environment it is advisable to shower and change clothes
Eyes/face	Wear safety goggles or safety glasses with side shields.

SECTION IX. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE	Solid
APPEARANCE AND ODOR	Grey/green fibrous batt or board; may have slight resin odor
BOILING POINT	N/A
MELTING POINT	Approx. 2150 °F (1177 °C)
VAPOR PRESSURE	N/A
VAPOR DENSITY (Air = 1)	N/A
SPECIFIC GRAVITY (g/cm³ @ 20 °C)	N/A
EVAPORATION RATE	N/A
FREEZING POINT	N/A
VISCOSITY	N/A
SOLUBILITY	Insoluble (H ₂ O)
PARTIAL COEFFICIENT	N/A

SECTION X. STABILITY AND REACTIVITY

STABILITY: Stable.
CHEMICAL INCOMPATIBILITIES: This product reacts with hydrofluoric acid.
THERMAL DECOMPOSITION PRODUCTS: Primary combustion products of the cured urea extended phenolic formaldehyde binder, when heated above 390 °F (200 °C), are carbon monoxide, carbon dioxide, ammonia, water and trace amounts of formaldehyde. Other undetermined compounds could be released in trace quantities. Emission usually only occurs during the first heating. The released gases may be irritating to the eyes, nose and throat during initial heat-up. Use appropriate respirators (air supplied) particularly in tightly confined or poorly ventilated areas during initial heat-up.
CONDITIONS OF REACTIVITY: Non-reactive
HAZARDOUS POLYMERIZATION: Will not occur.

SECTION XI. TOXICOLOGICAL INFORMATION

Acute Toxicity:

Coarse fibers and dust from mineral wool products can cause temporary mechanical irritation (itching, redness) of the skin, and of the mucous membranes in the eyes and in the upper respiratory tract (nose and throat). The itching and possible inflammation are a mechanical reaction to dust and coarse fibers (of more than about 5 µm in diameter), and are not damaging in the way chemical irritants may be. They generally abate within a short time after the end of exposure. When products are handled continually, the skin itching generally diminishes.

Chronic Toxicity:

Summary: In October 2001, IARC completed a re-evaluation of respirable mineral wool fibers and classified them in Group 3 (not classifiable as to their carcinogenicity to humans). A summary of the most important scientific studies appears below:

Human Data:

The possible carcinogenic effects of exposure to mineral wool fibers has been evaluated in a number of epidemiological (human) studies. Most of this research, including large long-term studies of mineral wool production workers in the U.S. and Europe, has been sponsored or supported by the North American and International thermal insulation industries, including Roxul Inc. Published reports of the early results of these studies identified significantly elevated rates of respiratory cancer in several subcohorts of the worker populations under evaluation (e.g., Simonato et al. 1987; Enterline et al. 1987). However, the studies had several methodological limitations, including failure to control for confounding exposures to other possible causes of the elevated cancer risk, including tobacco use and occupational exposures to recognized carcinogens such as asbestos. For these reasons, the authors of these reports did not interpret the results as establishing an association between exposure to mineral wool fibers and an increased risk of cancer. Several of these earlier reports formed part of the basis for IARC's previous classification of mineral wool fibers in Group 2B (possibly carcinogenic to humans) (IARC 1987).

Follow-up studies, including case-control studies designed to exclude the contribution of confounding exposures to the cancer experience of the study populations, found no evidence that mineral wool fibers are associated with an increased cancer risk (Marsh et al. 1996; Wong, et al. 1991; Kjaerheim et al. 2001). In announcing the new Group 3 classification for mineral wool fibers, IARC stated: "Epidemiologic studies published during the 15 years since the previous IARC Monographs review of these fibers in 1988 provide no evidence of increased risks of lung cancer or of mesothelioma (cancer of the lining of the body cavities) from occupational exposures during manufacture of these materials" (IARC 2001).

Animal Data:

Several studies of intraperitoneal injection of high doses of mineral wool fibers have produced significant increases in the incidence of mesothelioma (IARC 2002). The intraperitoneal injection studies formed part of the basis for IARC's previous (IARC 1987) Group 2B classification for mineral wool fibers. Leading scientists agree that intraperitoneal injection studies (i.e., surgical implantation or injection into the chest or abdomen) are the least relevant type of animal study for evaluating potential human risk for fiber exposures, because such studies bypass the animals' natural defense mechanisms and involve a type and pattern of exposure (implantation of a high dose early in life) that does not mimic human patterns of exposure (inhalation of much lower doses over a lifetime) (National Research Council 2000).

A well-designed long-term inhalation study in rats exposed to mineral wool fibers found no significant increase in lung tumor incidence, and no mesotheliomas (IARC 2002). Likewise, in two intratracheal instillation studies of mineral wool fibers, no significant increase in the incidence of lung tumors or mesotheliomas was found (IARC 2002). Inhalation studies are regarded as the most relevant type of animal data for evaluating potential human risk, and intratracheal instillation studies, while less relevant, are considered valuable for the initial screening of fibrous compounds (National Research Council 2000). Thus, evaluating all the available animal studies in conjunction with the human data, IARC's most recent review finds "inadequate evidence overall for any cancer risk" from mineral wool fibers (IARC 2001).

Evaluations of Potential Carcinogenicity:

Source	Classification	Description
IARC	Group 3	Not classifiable as human carcinogen.
ACGIH	Group A3	Confirmed animal carcinogen with unknown relevance to humans

SECTION XII. ECOLOGICAL INFORMATION

Ecotoxicity:

No data available for the products. The products are stable, are not expected to cause harm to animals, plants or fish, and have no other known adverse environmental effects.

Environmental Fate:

No data available for the products.

SECTION XIII. DISPOSAL CONSIDERATIONS

US EPA Waste Number & Descriptions:

General Product Information: The products, as supplied, are not expected to be a characteristic hazardous waste under RCRA if discarded.

EPA Waste Numbers: No EPA Waste Numbers are applicable for this product's components.

Disposal Instructions:

Product is not considered a hazardous waste. Dispose of waste material according to Federal, State, Provincial, and Local environmental regulations.

SECTION XIV. TRANSPORTATION INFORMATION

General:

No special precautions.

US DOT Information:

This product is not classified as a hazardous material for transport.

SECTION XV. REGULATORY INFORMATION

U.S. Regulations:

Toxic Substances Control Act (TSCA):

All components in this product are listed, as required, on the US EPA TSCA inventory, or are not required to be listed

CERCLA:

Includes mineral fiber emissions from facilities manufacturing or processing glass rock or slag fibers (or other mineral derived fibers) of average diameter 1 micrometer or less; Statutory RQ = 1 pound (.454 kg); no final RQ is being assigned to the generic or broad class (related to Fine mineral fibers).

Clean Air Act:

Mineral wool fiber appears on the Clean Air Act-1990 Hazardous Air Pollutants List.

State and Local Regulations:

State, Provincial, and Local regulations not identified in this Material Safety Data Sheet may apply.

WHMIS:

The products have been classified in accordance with the hazard criteria of the Controlled Product Regulations and this Material Safety Data Sheet contains all the information required by the Controlled Product Regulations

WHMIS IDL: No components are listed on the IDL

WHMIS Classification: No components are classified as controlled products.

SECTION XVI. OTHER INFORMATION

Glossary:

ACGIH: American Conference of Governmental Industrial Hygienists

ANSI: American National Standards Institute

ASTM: American Society for Testing and Materials

CAS: Chemical Abstract Services

CFR: Code of Federal Regulations (United States)

CSA: Canadian Standardisation Association

DOT: Department of Transportation (United States)

DSL: Domestic Substances List (Canada)

EPA: Environmental Protection Agency (United States)

HMIS: Hazardous Material Information System

IARC: International Agency for Research on Cancer

LC₅₀: (Lethal concentration₅₀) Concentration of a substance in air that causes dead of 50% mortality of a defined animal population

LD₅₀: (Lethal dose₅₀) Single dose of a substance that, when administered by a defined route in an animal assay, is expected to cause the death of 50% of a defined animal population.

NFPA: National Fire Protection Association (United States)

NIOSH: National Institute for Occupational Safety and Health

SECTION XVI. OTHER INFORMATION

Glossary:

NTP: National Toxicology Program
OSHA: Occupational Safety & Health Administration (United States)
PEL: Permissible Exposure Limit
RCRA: Resource Conservation and Recovery Act (United States)
RTECS: Registry of Toxic Effects of Chemical Substances
TDG: Transportation of Dangerous Goods
TLV: Threshold Limit Value
TWA: Time-weighted average
TSCA: Toxic Substances Control Act (United States)
WHMIS: Workplace Hazardous Materials Information System (Canada)

Reference:

Supplier MSDS

This MSDS has been prepared by: SOPREMA, INC.
For information: 800-543-3085

The Material Safety Data Sheets of SOPREMA are available on Internet at the following site: [HTTP://WWW.SOPREMA.US](http://WWW.SOPREMA.US)

Justification of the update:

New MSDS.

This MSDS contains all the information required by ANSI Z-400.1-1998 standard (United States), by regulation 29 CFR Part 1910.1200 of the Hazard Communication Standard of OSHA, and is in accordance with standard DORS/88-66 OF WHMIS Canada.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier or any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.