

POWER TOOL CLEAN TUBE STEEL PER SSPC-SP3. EXTEND SURFACE PREP MAX. 1/4" BEYOND LINE OF ALSAN REINFORCEMENT & COVER W/ ALSAN LIQUID MEMBRANE RESIN.


ALSAN FULLY REINFORCED LIQUID MEMBRANE (FLASHING GRADE) SKIRT WRAPPED AROUND PIPE W/ 2" (5cm) MIN. OVERLAP.

ALSAN FULLY REINFORCED LIQUID MEMBRANE COLLAR CUT INSIDE DIAMETER SAME SIZE AS PIPE DIAMETER (SEE NOTE #2).

FULLY ADHERED SBS MEMBRANE SYSTEM (AS SPECIFIED).

NOTES:

1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.
2. A FULLY REINFORCED LIQUID MEMBRANE SYSTEM IS DEFINED AS AN ASSEMBLY CONSISTING OF TWO LIQUID RESIN APPLICATIONS & FABRIC REINFORCEMENT INSTALLED BETWEEN THE RESIN LAYERS. REFER TO DETAIL A-1 FOR ADDITIONAL INFORMATION.

		310 QUADRAL DRIVE WADSWORTH, OHIO 44281 (330) 334-0066					
		TITLE PIPE PENETRATION FLASHING OVER MOD BIT					
SCALE	NONE	DWN	PBF	CHK	KD	APPROVAL DATE	11/11/10
DRAWING NUMBER	P-1M					REV	0

** USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.