



AQUADERE

AQUADERE (09D)

Order No. S73225*

Order No. S73225-A**

*For 1,000 Liter Tote (263 gallon)

**For five (5) gallon cans, (19L)

DESCRIPTION & APPLICATION

Aquadere is a polymer emulsion-based primer designed to improve the adhesion of heat welded, hot asphalt and cold adhesive applied roofing and waterproofing membranes. Aquadere is applied to properly prepared horizontal and vertical surfaces prior to installation of flashing base membrane plies being installed. Acceptable surfaces are clean and dry concrete, metal, wood, or acceptable gypsum substrates. Aquadere can be used to prime the top surface of either an SBS base or inner ply prior to the flashing cap membrane being installed. Aquadere may be brush, roller, or spray applied.

Aquadere Features and Benefits:

- May be used to prime base or ply sheet prior to installation of the ply or cap membrane.
- Brown when applied and black when ready to receive the membrane.
- Dries in one hour at 86° F (30° C) and three hours at 41° F (5° C).
- **Zero VOC's.**
- May be used anywhere Elastocol 500 is used over concrete, metal, or wood.
- In lieu of solvent-based primers, Aquadere is a water-based primer that meets or exceeds the performance of ASTM D41 primers, as tested and approved for use with Soprema, Inc. modified bitumen membranes.

Aquadere Limitations:

- Must be stirred or agitated before use.
- Store between 41° F (5° C) and 104° F (40° C); If stored at freezing; two days maximum at 32° F (0° C); it must be returned to 41° F (5° C) before use.
- This product is not suitable for plastic surfaces such as vinyl or water repellent treated panels.
- May not be used with self-adhered membranes.
- Minimum application temperature is 41° F (5° C) and rising.
- DO NOT THIN.

COVERAGE & PACKAGING

Product/ Property	AQUADERE
Description	Brown liquid (dries black)
Installation	brush, roller, or spray
Packaging	5 gallon (18.9 L) pail or 263 gal. (1,000 L) tote
Application	100 - 200 ft ² /gal (0.4 - 0.8 L/m ²) depending on surface & porosity

WARRANTY

Contact your local SOPREMA representative for project warranty offerings.