



# ELASTOCOL 600c

ELASTOCOL 600c (09)

Order No. D38745\*

\*For five (5) gallon cans, (19L)

## DESCRIPTION & APPLICATION

Elastocol 600c SA Primer is a blend of natural resins, solvent/synthetic rubber and is used on horizontal and vertical properly prepared, clean and dry concrete, metal or wood substrates prior to self-adhered field and flashing base membrane plies being installed. It is also used in priming either a high brush sanded SBS inner ply or base ply flashing prior to the self-adhesive flashing cap membrane ply being installed. The substrate must be clean, dry, and free of dust, grease or other contaminants Elastocol 600c is available in a "spray" container, Order No. D216.

See published Specifications and Approved Details.

During hot periods of the year, the self-adhesive base or inner ply and cap sheet are rolled out onto the dry substrate, set and re-rolled (scroll method). Then Elastocol 600c or other approved self-adhered primer are applied to the horizontal surface. After drying, the release film of the scrolled layer of self-adhesive membrane is removed and the membrane is matted onto the primed substrate with these steps being repeated for each succeeding layer.

## COVERAGE & PACKAGING

Product/ Property	ELASTOCOL 600c
Installation	brush, roller, or spray
Packaging	5 gallon (18.9 L)
Application	100 - 150 ft <sup>2</sup> /gal (0.4 - 0.6 L/m <sup>2</sup> ) depending on surface & porosity

## WARRANTY

Contact your local SOPREMA representative for project warranty offerings.