



ELASTOCOL STICK H₂O

ELASTOCOL STICK H₂O (09A)

Order No. D30100*

*For five (5) gallon cans, (19L)

DESCRIPTION & APPLICATION

Elastocol Stick H₂O is a polymer emulsion-based primer designed to improve the adhesion of self-adhesive waterproofing membranes on horizontal and vertical properly prepared, clean and dry concrete, metal, wood, acceptable gypsum or polystyrene substrates prior to installation of self-adhered field and flashing base membrane plies being installed. Elastocol Stick H₂O Primer is not intended for use in priming either an SBS base or inner ply prior to the flashing cap membrane being installed. Elastocol Stick H₂O Primer may be brush, roller, or spray applied. Spraying equipment recommendations are a tip size between 20 and 25 mils with a continuous pressure setting of 1,300 psi.

Elastocol Stick H₂O Limitations:

- May not be used to prime base or ply sheet prior to installation of the ply or cap membrane.
- The cap membrane must be installed the same day as the base membrane.
- This product is not suitable for plastic surfaces such as vinyl or water repellent treated panels.
- KEEP FROM FREEZING.
- Minimum application temperature is 41° F (5° C).
- Dry time ranges from 30 minutes to 3 hours.
- May not be used to prime Sopraboard.

During hot periods of the year, the self-adhesive base or inner ply and cap sheet are rolled out onto the dry substrate, set and re-rolled (scroll method). Then Elastocol Stick H₂O or other approved self-adhered primer are applied to the horizontal surface. After drying, the release film of the scrolled layer of self-adhesive membrane is removed and the membrane is matted onto the primed substrate with these steps being repeated for each succeeding layer. See published Specifications and Approved Details.

COVERAGE & PACKAGING

Product/ Property	ELASTOCOL STICK H ₂ O
Description	polymer emulsion
Installation	brush, roller, or spray
Packaging	5 gallon (18.9 L)
Application	100 - 200 ft ² /gal (0.4 - 0.8 L/m ²) depending on surface & porosity

WARRANTY

Contact your local SOPREMA representative for project warranty offerings.