



# SOPRASTAR CHIPS

SOPRASTAR CHIPS

Order No. L-A160\*

\* 50 pound boxed sack

## DESCRIPTION & APPLICATION

**DESCRIPTION:**

Soprastar Chips are flat, angular pigmented polymer flakes suitable for broadcast.

**PRODUCT USES:**

Soprastar Chips are used to obscure bleedout of bitumen along side and head laps when installing Soprastar membranes.

**COLOR:**

Soprastar Chips are available in white only.

**PACKAGING:**

Soprastar Chips are available in fifty (50 lb) pound (22.68 kg) sacks.

**STORAGE:**

Always store in a clean and dry location. Product should not be dropped and seals should not be broken prior to use.

**APPLICATION:**

Soprastar Chips are applied into bituminous bleedout or adhesive while hot or liquid. Cool bleedout can be warmed utilizing an external heat source in order to reliquify bleedout to accept Soprastar Chips. Soprastar Chips should be applied to excess.

**COVERAGE RATES:**

One pallet of Soprastar (30 rolls) requires approximately fifty (50) pounds (22.68 kg) of Soprastar Chips to dress the side and end laps. Coverage rates are approximate and are dependent primarily upon the amount of bleedout. Bleedouts greater than three-eighths (3/8") inch (9.5 mm) will result in a higher consumption rate.