



SOPRAWALK

SOPRAWALK (81)

Order No. *

DESCRIPTION

SOPRAWALK walkway membrane is made up of a non-woven polyester reinforcement and elastomeric bitumen (SBS Modified Bitumen). The upper face is covered with colored granules. The underside is lightly sanded. SOPRAWALK is heat welded, hot asphalt or cold applied with a compatible trowel-grade adhesive. See published Specifications and Approved Details.

COMPOSITION & PACKAGING

Product/ Property	SOPRAWALK
Reinforcement	non-woven polyester with extra static & dynamic puncture resistance
Elastomeric Bitumen	selected blend of bitumen and SBS thermoplastic polymers
Topside	granules
Underside	lightly sanded
Approximate Nominal Thickness	200 mils (5.0 mm)
Approximate Roll Coverage	75 ft ² (7 m ²)
Side Lap	3" (76 mm)
End Lap	6" (152 mm)
Roll Length	26 feet (7.9 m)
Roll Width	39-3/8" (1 m)
Approximate Roll Weight	114 lbs (51.7 kg)
Rolls per Pallet*	25
* Rolls stacked upright on pallets	

WARRANTY

SOPRAWALK meets Soprema's manufacturing material specification requirements and carries a Material Only warranty.