



SOPRAGLASS M GR

SOPRAGLASS M GR (39A)

Order No. 01067*

*Cap sheet order number is for WHITE CAP SHEETS ONLY. Contact Customer Service or Sales Representative for other available cap sheet colors and special order requirements.

DESCRIPTION

SOPRAGLASS M GR is a fiberglass reinforced SBS modified bitumen membranes used to form asphalt applied (mopped) and cold adhesive applied two-ply roof assemblies.

SOPRAGLASS M GR is a granulated cap sheet. See published Specifications and Approved Details.

COMPOSITION

Product/ Property	SOPRAGLASS M GR
Reinforcement	fiberglass reinforcement
Elastomeric Bitumen	selected blend of bitumen and SBS thermoplastic polymers
Topside	colored granules
Underside	sanded
Approximate Nominal Thickness	136 mils (3.4 mm)
Approximate Roll Coverage	195 ft ² (18.2 m ²)
Side Lap	3" (76 mm)
End Lap	6" (152 mm)
Roll Length	65.9 ft (20 m)
Roll Width	39" (1 m)
Approximate Roll Weight	102 lbs (46.3 kg)
Rolls per Pallet*	30
* Rolls stocked upright on pallets	

WARRANTY

Contact your local Soprema representative for project warranty offerings.