



SOPRAGLASS GR

SOPRAGLASS GR (39B)

Order No. 08400*

*Cap sheet order number is for WHITE CAP SHEETS ONLY. Contact Customer Service or Sales Representative for other available cap sheet colors and special order requirements.

DESCRIPTION

SOPRAGLASS GR is a fiberglass reinforced oxidized bitumen membrane used to form asphalt applied (mopped) and cold adhesive applied two-ply roof assemblies. SOPRAGLASS GR complies with ASTM D 4897 criteria (as a venting base sheet) when installed granule-side down/sanded-side up and is mechanically fastened in place.

SOPRAGLASS GR is a granulated cap sheet. See published Specifications and Approved Details.

COMPOSITION

Product/ Property	SOPRAGLASS GR
Reinforcement	fiberglass reinforcement
Bitumen	oxidized asphalt
Topside	colored granules
Underside	sanded
Approximate Nominal Thickness	96 mils (2.4 mm)
Approximate Roll Coverage	123 ft ² (11.4 m ²)
Side Lap	3" (76 mm)
End Lap	6" (152 mm)
Roll Length	41 ft (12.5 m)
Roll Width	39" (1 m)
Approximate Roll Weight	103 lbs (46.81 kg)
Rolls per Pallet*	25
* Rolls stocked upright on pallets	

WARRANTY

Contact your local Soprema representative for project warranty offerings.