



ALSAN ACCELERATOR

Alsan Accelerator

Order No. D30230

DESCRIPTION & APPLICATION

ALSAN TRAFIK HP traffic coating system is a polyurethane membrane designed to waterproof vehicular and pedestrian traffic areas on concrete decks. It can also be installed on plywood decks for balconies. This system is composed of three products for light pedestrian traffic and of four products for vehicular traffic:

ALSAN ACCELERATOR is added to ALSAN TRAFIK HP 520 to accelerate curing.

PACKAGING:

ALSAN ACCELERATOR is supplied in 100 ml cans. For ordering purposes, for every pallet of ALSAN TRAFIK HP 520 (36 five-gallon cans) two boxes of ALSAN ACCELERATOR (18 cans per box) should be ordered.

STORAGE:

Shelf life: 6 months in original unopened container. Always store closed containers in cool, ventilated and dry location away from heat and oxidizing agents. Do not store in direct sunlight or in temperatures below 32°F (0°C) or above 77°F (25°C). Storing the containers above the recommended temperature may reduce the product's shelf life. The resin may polymerize at temperatures above 140°F (60°C).

HANDLING:

Always use caution when handling the products. Do not smoke. Keep away from open flame, fire or any ignition source. Avoid skin and eye contact with this product. Cured product may be disposed of in standard landfills. Uncured product is considered a hazardous material and must be handled as such, in accordance with local, state and federal regulations.

APPLICATION:

Pre-mix one can (100 ml) of ALSAN ACCELERATOR to one can (5 gallons) of Alsan TRAFIK HP 520 prior to application of ALSAN TRAFIK HP 520.

ALSAN ACCELERATOR is used exclusively with ALSAN TRAFIK HP 520 and should not be combined with any other ALSAN product.

TECHNICAL INFORMATION

COVERAGE RATES

ALSAN TRAFIK HP 520	minimum 1.7 gal/100 ft ² (28 wet mils)	300 ft ² per 5 gallon can
---------------------	---	--------------------------------------

See recommendations for specific applications. Yields will vary depending upon substrate condition.