



ALSAN CLEANER

DESCRIPTION & APPLICATION

Soprema Alsan Cleaner is used to clean and reactivate the transition area of in-place Soprema Alsan liquid-applied one-component polyurethane membranes at tie-ins, repairs and between staged coats of resins. Soprema Alsan Cleaner may also be used as solvent for cleaning spills, tools and equipment.

Soprema Alsan Cleaner should be applied using clean rags or cloth. After cleaning, the solvent should be allowed approximately 15-minutes to evaporate, directly followed by liquid-applied membrane application. Refer to Soprema Alsan liquid-applied one-component polyurethane resins technical information for specific applications.

Consumption will vary depending upon condition of the surface, application and use.

CHARACTERISTICS

	ALSAN CLEANER
Physical State	Liquid solvent
Color	Colorless
Flash point	23°F (-5°C)
Odor	Strong

HANDLING AND STORAGE

Product is supplied in re-sealable 1 gallon and 5 gallon containers.

Always store product in cool and dry location away from any heat source. Do not store in direct sunlight or in temperature below 40°F (5°C) or above 77°F (25°C). Open with caution as contents may be under pressure. Product is highly flammable - keep away from heat, sparks and open flame source. Refer to Material Safety Data Sheet (MSDS) for personal protection, proper handling and storage.

Shelf life: 12 months in original unopened container.

When work is interrupted or completed, tools must be thoroughly cleaned with Soprema Alsan Cleaner before the product cures.



SPECIAL INDICATIONS

Safety Instruction:

- Product may be under pressure. Open with caution.
- Always use caution when handling the products. Do not smoke. Keep away from open flame, fire or any ignition source. Avoid skin and eye contact with this product.
- Cured resin may be disposed of in standard landfills. Uncured resin is considered a hazardous material and must be handled as such, in accordance with local, state and federal regulations.
- Workers must wear long sleeved shirts, long pants, work boots and use only butyl rubber or nitrile gloves when working with the product. Safety glasses with side shields are required for eye protection. Use of NOISH approved respirator is required if the airborne concentration exceeds recommended limits. For more information, refer to instruction on the label of the can and to relevant Material Safety Data Sheet (MSDS).

Quality control:

SOPREMA has always attached the highest importance to Quality Control. For this reason, we operate an internationally recognized Quality System according to ISO 9001:2000, with the system independently monitored and certified by AFAQ-Association Française d'Assurance Qualité (French Main Quality Certification Office).

GENERAL

SOPREMA is a Certified ISO 9001:2000 worldwide producer of bituminous membranes and a manufacturer of liquid membrane systems with factories in Europe and North America. Waterproofing sheets have been produced by SOPREMA since 1908. SOPREMA has been at the forefront of liquid membrane technology for nearly two decades.