



ALSAN ALL-PURPOSE CLEANER

DESCRIPTION & FEATURES

Soprema Alsan All-Purpose Cleaner is a water-based surface cleaner designed dissolve and remove heavy accumulations of hard-to-remove dirt, oil and grease without the use of harsh solvents. The exceptional cleaning and degreasing power of Soprema Alsan All-Purpose Cleaner exceeds that of the conventional water-based degreasers. When old, painted surfaces are cleaned with Alsan All-Purpose Cleaner, the product promotes adhesion as it cleans. In some cases, Sanding, solvent wiping, grit sweeping and scarrifying painted surfaces may be eliminated.

Soprema Alsan All-Purpose Cleaner can be used to clean aluminum, galvanized metal and other surfaces prior to painting or coating. Also effective when used prior to abrasive blasting or application of wetting primers to remove grease, oil, chlorides or other contaminants.

Advantages:

- Promotes adhesion as it cleans
- Powerful solvent-free degreaser
- Improves recoatability of aged and painted surfaces
- Biodegradable
- Easy to apply, low-odor
- Contains no phosphates, halogens or alkali hydroxides
- Contains no lead or mercury containing materials.

CHARACTERISTICS

Color	Clear to slightly hazy
Container sizes	1 or 5 Gallon pails
Weight per Gallon	8.6 lbs/Gallon (1.03 kg/L)
VOC (EPA 24)	0.0 lbs/Gallon (0 g/L)
Minimum Dry-Time	Do not allow to dry
pH Level:	11.0 - 13.5
Clean-up Solvent	Water

DIRECTIONS FOR USE

For most applications, Soprema Alsan All-Purpose Cleaner can be reduced 2 or 3 times with fresh, clean water. Test cleaning a small area may be used to determine proper dilution levels and to insure compatibility with the substrate. Adequate protective equipment and clothing such as rubber gloves and protective eyewear are recommended. Apply the solution with brush, roller, mop or low pressure spray. If surface is hot, wet before applying cleaner solution. Moderate scrubbing will aid in performance and speed of cleaning. Allow cleaner to remain for five to ten minutes, but do not allow the surface to dry. Rinse with large amounts of clean water. For large surfaces, rinsing with a power washer (1500 psi minimum) is recommended. A thorough rinsing is very important. All of the Soprema Alsan All-Purpose Cleaner must be removed. Do not allow the cleaner to dry on the surface. When completely removed, the surface will no longer foam when rinsed. Allow the surface to dry thoroughly before applying any coatings.



PRECAUTIONS

WARNING! CAUSES EYE AND SKIN BURNS. CAUSES RESPIRATORY TRACT IRRITATION. HARMFUL OR FATAL IF SWALLOWED. ASPIRATION HAZARD-CAN ENTER LUNGS AND CAUSE DAMAGE. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN.

If sanding is done, wear a dust mask to avoid breathing of sanding dust. Do not breathe vapors or spray mist. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use.

FIRST AID: In case of skin contact, wash off quickly with plenty of soap and water, remove contaminated clothing. For eye contact flush immediately with large amounts of water, for at least 15 minutes. Obtain emergency medical treatment. If swallowed, obtain medical treatment immediately. If inhalation causes physical discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, get medical help. **KEEP FROM FREEZING.** breathing difficulty occurs, get medical help. **KEEP FROM FREEZING.**

For additional safety information, refer to the Material Safety Data Sheet for this product.

Shelf Life: 24 months minimum when stored at 77°F (25°C) and unopened.

GENERAL

SOPREMA is a Certified ISO 9001:2000 worldwide producer of bituminous membranes and a manufacturer of liquid membrane systems with factories in Europe and North America. Waterproofing sheets have been produced by SOPREMA since 1908. SOPREMA has been at the forefront of liquid membrane technology for nearly two decades.