


- NOTES:
1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS AND APPROVED DETAILS. FOR BUILDINGS; LESS THAN 60' IN HEIGHT IN GROUND ROUGHNESS CATEGORIES 'B' AND 'C' AND MAX. 90 MPH WIND ZONE WITH FMG APPROVED 22 GA STEEL OR CONCRETE DECKS. FOR FASTENER SPACING ON OTHER DECK TYPES, CONTACT SOPREMA CORPORATE TECHNICAL DEPARTMENT. THIS DETAIL DEPICTS ONLY SOPRAFIX LAYOUT; AFTERWARD CAPSHEET IS ADHERED BY HOT MOPPING, HEAT WELDING, COLD ADHESIVE OR COLSTIX™ SELF-ADHERED APPLICATION METHODS.
 2. THIS SOPRAFIX DETAIL IS **APPROVED FOR STANDARD WARRANTY COVERAGE-NO WIND RIDERS.**
 3. PERIMETER DEFINITION: X=4/10 OF BUILDING HEIGHT OR 1/10 THE BUILDING WIDTH, WHICHEVER IS THE LESSER DIMENSION, WITH A MINIMUM OF 2 PERIMETER ROLLS.

(SEE DETAIL SFMA-005)

		310 QUADRAL DRIVE	
		WADSWORTH, OHIO 44281 (330) 334-0066	
TITLE Basic Soprafix-e Perimeter & Corner 2			
SCALE NONE	DWN DMT	CHK BS	APPROVAL DATE 11/17/06
DRAWING NUMBER SFMA-008			REV 0

** USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.