



- ⊙ IN-LAP FASTENER & STRESS PLATE
- ⊙ FASTENER & STRESS PLATE AT BASE OF CURB, WALL OR OTHER PENETRATION.

NOTES:

1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS AND APPROVED DETAILS. FOR BUILDINGS: LESS THAN 60' HEIGHT IN GROUND ROUGHNESS CATEGORIES 'B' AND 'C' WITH MAX. 100 MPH WIND ZONE.
2. INSTALL SOPRAFIX FASTENER AND STRESS PLATE, PBB OR MBB AT BASE OF PENETRATIONS, WALLS AND ANGLE CHANGES. ONE SOPRAFIX MEMBRANE ROLL—USING PERIMETER FASTENING PATTERNS IS SECURED AROUND SPECIFIC SIZED PENETRATIONS. PARTIAL ROLLS RECEIVE SAME INCREASED FASTENER DENSITY.
3. THE PIPE DIMENSION DICTATES THE NUMBER OF FASTENERS EQUALLY SPACED AROUND THE PENETRATION, I.E. 4" DIA. => 4 FASTENERS, 8" DIA. => 8 FASTENERS.



310 QUADRAL DRIVE  
WADSWORTH, OHIO 44281  
(330) 334-0066

TITLE Warranty Wind Rider w/ Plates at Penetrations			
SCALE NONE	DWN DMT	CHK BS	APPROVAL DATE 11/17/06
DRAWING NUMBER SFMA-020			REV 0

\*\* USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.