


- METAL BATTEN BAR
- METAL BATTEN BAR AT BASE OF PARAPET WALL, CURB, OTHER PENETRATIONS OR ANGLE CHANGES

- NOTES:
1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS AND APPROVED DETAILS. FOR BUILDINGS; LESS THAN 60' IN HEIGHT IN GROUND ROUGHNESS CATEGORIES 'B' AND 'C' WITH MAX. 120 MPH WIND ZONE.
 2. ALL CURBS, PARAPET WALLS AND OTHER PENETRATIONS MUST RECEIVE PERIMETER FASTENER SPACING WITH BATTEN BAR AT THE BASE OR ANGLE CHANGES.
 3. THE PIPE DIMENSION DICTATES HOW MANY FASTENERS ARE USED IN THE BATTEN BAR. ALL SIDES ARE SECURED WITH BATTEN BAR.
 4. BASIC SOPRAFIX IS ONLY **APPROVED FOR STANDARD WARRANTY COVERAGE—NO WIND RIDERS.**

		310 QUADRAL DRIVE	
		WADSWORTH, OHIO 44281	
		(330) 334-0066	
TITLE Metal Batten Bar Fastening @ Penetrations			
SCALE NONE	DWN DMT	CHK BS	APPROVAL DATE 8/13/07
DRAWING NUMBER SFMA-039			REV 0

** USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.