

HEAT WELDED OR HOT AIR WELDED OR ADHERED WITH SOPREMA 2-PART MEMBRANE ADHESIVE (TYPICAL)

METAL CAP SECURED AS REQUIRED BY AHJ

FIRST FLASHING MEMBRANE PLY OR FIRE RESISTANT SHEET

MECHANICALLY FASTENED SOPRALENE GRANULATED MEMBRANE WALL COVERING WITH SOPREMA APPROVED FASTENER AND BATTEN BAR SECURED AS REQUIRED BY AHJ

6" (152mm)

TYP. (102mm) 4" MIN 5" (127mm)

FASTENERS APPROX. 8" (203mm) O.C. OR BOTH PLIES FASTENED SIMULTANEOUSLY

SOPRAFIX FASTENED 12" O.C.

ON HEAT WELDED FLASHINGS EMBED GRANULES IN FLASHING AREA.


SOPRAFIX BASE MEMBRANE PLY, FASTENED PER CURB, WALL AND PERIMETER LAYOUT DETAILS.

WOOD NAILERS INSTALLED WITH BOND BREAKERS AND FASTENED AS SPECIFIED OR REQUIRED BY CODE OR INDUSTRY STANDARDS TO RESIST DESIGN LOADS AND CORROSION OF STEEL DECKING, FASTENERS AND METAL EDGING.

THERMAL INSULATION, COVER BOARD AND ROOFING APPLIED TO DECK AS SPECIFIED OR REQUIRED

NOTES:

1. DETAIL TO BE USED IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS, APPLICATION METHODS AND APPROVED DETAILS.
2. SOPREMA ADHESIVES, CEMENTS, MASTICS, PRIMERS AND SEALANTS ARE REQUIRED WHERE INDICATED.

		310 QUADRAL DRIVE	
		WADSWORTH, OHIO 44281 (330) 334-0066	
TITLE MEMBRANE WALL COVERING WITH SOPRAFIX			
SCALE NONE	DWN DMT	CHK BS	APPROVAL DATE 3/27/06
DRAWING NUMBER SFWBF-008			REV 0

\*\* USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.

FILE NAME: WP1677 PLOT DATE: 3/27/06