

- ADJUSTABLE SUPPORT BRACKET WITH ROLLER
- SET BOLTS IN ELASTOMERIC SEALANT
- METAL CAP
- FASTENERS APPROX. 8" O.C. (203mm)
- POLYESTER REINFORCING MEMBRANE PLY ADHERED TO CURB AND ONTO BASE PLY WITH SEALED LAPS
- PRIME MASONRY SUBSTRATE, ON HEAT WELDED FLASHINGS, FASTEN SOPREMA APPROVED BASE SHEET 8" (203mm) O.C. IN GRID PATTERN AND AT SIDE LAPS.
- ON HEAT WELDED FLASHINGS EMBED GRANULES IN FLASHING AREA
- CAP MEMBRANE FLASHING PLY
- FIRST MEMBRANE FLASHING PLY
- FIELD CAP MEMBRANE PLY
- SOPRAFIX FIELD BASE MEMBRANE PLY MECHANICALLY FASTENED IN-LAP WITH TRI-FIXX SYSTEM

WOOD NAILERS AND CANT (IF REQUIRED) FASTENED AS SPECIFIED, TYP.


TRI-FIXX PLATE AND FASTENERS 8" O.C. (203mm)

THERMAL INSULATION /LWIC

ROOF DECK

NOTES:

1. USE IN CONJUNCTION WITH SOPREMA GENERAL REQUIREMENTS AND APPROVED DETAILS WHILE CONSTRUCTING OTHER ROOF COMPONENTS TO EXCEED CURRENT EDITION REQUIREMENTS OF FM APPROVALS, SMACNA, NRCA, ANSI/SPRI ES-1 AND FLORIDA BUILDING CODE-RAS NO. 111 WITH THE MOST STRINGENT REQUIREMENTS OR RECOMMENDATIONS PREVAILING.

		310 QUADRAL DRIVE	
		WADSWORTH, OHIO 44281	
		(330) 334-0066	
TITLE TRI-FIXX FASTENING @ PIPE SUPPORT CURB			
SCALE	DWN	CHK	APPROVAL DATE
NONE	DMT	PR	10/15/04
DRAWING NUMBER TFPN-002			REV 0

** USAGE OF THIS DRAWING IS GOVERNED BY THE TERMS OF SERVICE FOR SOPREMA DETAIL. PLEASE CONSULT THESE TERMS OF SERVICE PRIOR TO UTILIZING THIS DRAWING.